

Technical Data Sheet

Interflon Degreaser EM56+

High yielding, heavy duty industrial degreaser

Powerful, slow evaporating industrial degreaser with F-Active Technology. Very suitable for cleaning and degreasing machines, parts and surfaces that are heavily soiled with dried oil and grease residues. Rapidly breaks down grease, oil and other hydrocarbons. Leaves behind a protective layer that protects against rust.

Applications

Cleaning and (cold) degreasing of chains, gears, bearings, motors, machines, conveyors, sliding surfaces, steel plates, (ship) floors and many other surfaces and machine parts.

Advantages

- ⦿ Excellent degreasing and cleaning effect
- ⦿ Protective film against corrosion
- ⦿ Can be rinsed with water
- ⦿ Short emulsion time in oil-water separators
- ⦿ Slow evaporation rate

Instructions for use

Do not dilute the product. Interflon Degreaser EM56+ can be applied manually (i.e. brush) as well as by plunging or spraying. The best result is obtained by first applying the cleaner for 10 to 20 minutes and then brush or wipe off. If required, rinse the surface with water. Does not affect lacquer and synthetic material. Also NBR and neoprene rubbers are not affected. Can be sprayed using a trigger spray. The trigger spray will perish in time.

It is advisable to test a small inconspicuous area to make sure that the cleaning agent does not adversely affect or damage the surface being cleaned. Do not apply to hot surfaces. When cleaning large vertical areas, apply the product from the bottom and work upwards ensuring that the whole area is covered. Cleaning away any dirt is best done from the top in a downwards direction to prevent leaving any streak marks. Do not use the product or allow to dry in direct sunlight.

Property	Result	Method
Composition	Mixture of solvents and additives	
Colour	Colourless	
Odour	Characteristic	
Density 20°C	0.76 g/cm ³	
Highest application temperature	40°C	
Manufacturing date	The batch number consists of a 8-digit number. The first 4 numbers represent the YY/MM of the manufacturing.	
Shelf life*	2 years	
Evaporation speed	0.05 (n-BuAc = 1)	
Vapour pressure 20°C	0.6 hPa	
Halal	Yes	
Kosher	Yes	

* Shelf life of the product in original and unopened packaging. Storage temperatures <0°C need to be avoided to guarantee product quality.

This information is based on our best and present knowledge and intended to provide general notes about the product and intended use. Therefore it shouldn't be construed as guaranteeing properties of the product described or suitability for an application. Any existing industrial property rights must be observed. Quality of our products is guaranteed under our General Conditions of Sale. Interflon® and MicPol® are registered trademarks of Interflon BV. Typical properties mentioned in this document are based on our production tolerances and do not represent a specification. Variations that do not affect product performance are to be expected during normal manufacturing. Information provided in this document is subject to change without notice in advance.